

# VWR® Examination Gloves PRODUCT SPECIFICATIONS



## **VWR Powder-Free Nitrile Examination Gloves**

- Glove type: non-powdered ambidextrous gloves with straight fingers, beaded cuff, and fully textured finish
- · Material: 100% nitrile
- Packaging: 100 gloves (±2) per dispenser box, 10 boxes per case
- · Color: light blue

Manufactured from 100% premium nitrile, VWR Powder-Free Nitrile Examination Gloves provide hand protection against biohazards and a broad range of chemicals. These nonsterile, examination-grade gloves are fully textured to provide a secure grip. Gloves are rigorously tested and manufactured under stringent process controls according to ISO 9001 and ISO 13485 to ensure that each product meets exacting quality standards. Our products are lot controlled and validated through independent lab testing.

#### **VWR Powder-Free Nitrile Examination Gloves**

| Size    | Cat. No.  | Pack of | Case of  |
|---------|-----------|---------|----------|
| X-Small | 82026-423 | 100     | 10 Packs |
| Small   | 82026-424 | 100     | 10 Packs |
| Medium  | 82026-426 | 100     | 10 Packs |
| Large   | 82026-428 | 100     | 10 Packs |
| X-Large | 82026-430 | 100     | 10 Packs |

### **Technical Data**

CLEANLINESS
Particles (µg/glove)

| Test Item           | Result    |  |
|---------------------|-----------|--|
| DIMENSIONS          |           |  |
| Overall Length (mm) | 230       |  |
| Palm Width (mm)     |           |  |
| X-Small             | 70–92     |  |
| Small               | 80–92     |  |
| Medium              | 90–102    |  |
| Large               | 110–112   |  |
| X-Large             | 110–122   |  |
| Thickness (mm)      |           |  |
| Finger              | 0.11-0.17 |  |
| Palm                | 0.09-0.15 |  |
| Cuff                | 0.07-0.13 |  |
| Weight (g)          |           |  |
| X-Small             | 3.7-4.3   |  |
| Small               | 4.2-4.8   |  |
| Medium              | 4.7–5.3   |  |
| Large               | 5.2-5.8   |  |
| X-Large             | 5.7-6.3   |  |

| PHYSICAL PROPERTIES     |     |  |
|-------------------------|-----|--|
| Tensile Strength (MPa)  |     |  |
| Before Aging            | 14  |  |
| After Aging             | 14  |  |
| Ultimate Elongation (%) |     |  |
| Before Aging            | 500 |  |
| After Aging             | 500 |  |

# **Quality Standards**

- Meet or exceed ASTM D6319-00a as well as EN 455-1 and -2 on dimensions and water leak properties
- Meet or exceed AS 4011



Prices, product appearance and specifications are current at the time of printing, subject to change without notice. Availability for certain products may be limited by federal, state, provincial or local licensing requirements. VWR makes no claims or warranties concerning sustainable/green products any claims concerning sustainable/green products are the sole claims of the manufacturer and not those of VMR International, LLC. All prices are in U.S. dollars unless otherwise noted. Offers valid in USA and Canada, void where prohibited by law or company policy, while supplies last, Visit vw.com to view our privacy policy and additional disclaimers.

WWR, forms of VWR, and the WWR logo and/or design are either registered trademarks ®, trademarks ™, or service marks <sup>24</sup> of VWR International, LLC in the United States and/or other countries. All other marks referenced herein are registered trademarks, trademarks or service marks of their respective owner(s). For a complete list of trademark owners please visit vwr.com.

©2010 VWR International, LLC. All rights reserved.